

- One screw design
- Bezel-Free True Flat PCAP touch
- MSR / I-Button / RFID / Finger printer optional
- VFD customer display / 9.7" True-Flat LED monitor / 9.7" True-Flat touch monitor optional
- Multiple choice motherboard
- Mounted / Desktop type optional
- Slim stand
- Multiple interfaces
- Easy disassemble



Support HD camera



Specification

CPU	Intel®Celeron® Bay Trail D J1900 Quad Core 2.0G up to 2.42G,2M Cache 10W(Fanless)	Intel Celeron 3865U Dual Core 1.80G 2M Chache 15W	Intel®Core™ i3-6100U, Dual Core 2.30G, 3M Cache 15W(Fanless)
Memory	2GB DDR3 1333MHz1* SO-DIMM slot up to 4GB		
HDD	MSATA32/64/128GB SSD or 2.5" 500GB HDD		
Size / Resolution	15" TFT-LED/ 1024×768		
Touch Screen	True flat PCAP touch screen		
Windows / Linux	Windows 7 / 8 / 10, POSReady 7,Ubuntu 13.04 LTS		
Card Reader	MSR / I-Button / RFID / Finger print		
Customer Display	VFD (2*20 Digits)		
2nd Display	9.7" True-flat LED monitor / 9.7" True-flat touch monitor		
Wireless Module	802.11a/b/g/n		
I/O Interface	Rj45x1,USB2.0x6,USB3.0x1,RS232x3,Rj11x1		
Certificates	CE,FCC Class A,RoHS,CB		
Working Temperature	0°C~40°C(32°F~104°F)		
Carton Size(mm)	425*185*420 (L*W*H)		
G.W	6.5KGS		