

- One screw design
- Bezel-Free True Flat PCAP touch
- MSR / I-Button / RFID / Finger printer optional
- VFD customer display / 9.7" True-Flat LED monitor / 9.7" True-Flat touch monitor optional
- Multiple choice motherboard
- Mounted / Desktop type optional
- Slim stand
- Multiple interfaces
- Easy disassemble



Support HD camera



Specification

CPU	Intel Celeron 3865U Dual Core 1.80G 2M Cache 15W
Memory	2GB DDR3 1333MHz1* SO-DIMM slot up to 4GB
HDD	MSATA32/64/128GB SSD or 2.5" 500GB HDD
Size / Resolution	15" TFT-LED/ 1024×768
Touch Screen	True flat PCAP touch screen
Windows / Linux	Windows 7 / 8 / 10, POSReady 7, Ubuntu 13.04 LTS
Card Reader	MSR / I-Button / RFID / Finger print
Customer Display	VFD (2*20 Digits)
2nd Display	9.7" True-flat LED monitor / 9.7" True-flat touch monitor
Wireless Module	802.11a/b/g/n
I/O Interface	Rj45x1, USB2.0x6, USB3.0x1, Rs232x3, Rj11x1
Certificates	CE, FCC Class A, RoHS, CB
Working Temperature	0°C~40°C(32°F~104°F)
Carton Size(mm)	425*185*420 (L*W*H)
G.W	6.5KGS