



Core i J1900 Amplicud, BIRCH 15.6" Wide all-in-one system

	STATE OF THE PARTY.	fications
4	noci	TICATIONS
9	DELI	IICULIUIIS

Main Board

CPU

Intel® Celeron® J1900, Quad core, clock speed 2.0GHz, TDP 10W

Intel® Core™ i5-4200U , Dual core, clock speed 1.6GHz up to 2.6GHz, TDP15W

Intel® Core™ i5-6200U , Dual core, clock speed 2.3GHz up to 2.8GHz, TDP15W

DDR3L-1333 MHz 4GB up to 8GB Intel® HD Graphics

DDR4-2666 MHz 4GB up to 8GB

LCD Panel

Panel Size 15.6" Maximum Resolution Brightness **Contrast Ratio** 

Response Time 1366 x 768 View Angles (H/V) 220 cd/m<sup>2</sup> **Touch Panel** 500:1

10 ms 90 / 65

**Projected Capacitive Touch** 

2.5" SATA III Interface x 1

Socket

mini-PCle (full size) + m-SATA (full size)

Power

**Power Adaptor** Input AC 100-240V 1.6A (MAX) 50/60Hz, Output DC 12V 5A

**USB 2.0 USB 3.0** Serial LAN

3 (optional to 5)

0 (optional to 2)

0 (optional to 2)

2nd VGA Output

One 15 Pin VGA Port

One Earphone & One Microphone

Power Button LED Indicators

One

Power (Red)

Magnetic Card Reader VFD customer display Second display RFiD reader

ISO Track 1/2/3, USB interface 20 x 2 characters, USB interface

8"TFT USB interface 13.56Mkz Mifare reader

With A2 Stand W/O Stand

399.6(W) X 193.9(L) X 294.3(H) mm 399.6(W) X 40(L) X 252.7(H) mm

**Operating Temperature** Storage Temperature **Operating Humidity** Storage Humidity

0°C ~ 40°C ( 32°F ~ 104°F ) - 20°C ~ 60°C ( - 4°F ~ 140°F) 10% - 80% RH non condensing

10% - 80% RH non condensing

**Ordering information** 



AP8[X]00-[XX]25G

15.6" Amplitud all-in-one system, P-CAP touch

[X] 1: J1900CPU 4: Core i5 -4200U 5: Core i5-6200U

[XX] 0: without stand. T: w/A2 desktop stand H: w/A4 stand

Optional peripherals: Triple MSR reader, iButton, RFID reader, VFD display, 2nd TFT display

ARDAX TECH GmbH Am Schiffbeker Berg 6 D-22111 Hamburg, Germany TEL +49 40 466 5624 0 FAX +49 40 466 5624 55 info@ardax-tech.eu

All products, brands or companies mentioned are tardemarks or registered trademarks of their respective companies. Specifications are subject to change without prior notice

www.ardax-tech.eu


# 15.6" AMPLITUD SYSTEM! COME INTO VOGUE.

15.6" TFT with 16: 9 ratio display all-in-one touch system comes popular standard in the commercial computing market, but they are far from satisfactory for professional applications on the" Automation" and "Vertical market" such as retail, F&B, industry.... or hospitality market

In an increasingly competitive market, the 15.6" Amplitud system is an ideal system for those who appreciated pro-

fessional features combined with state-of-the-art design and exceptional facilities.

It is a wallet-friendly system to own.



## Blessed with 15.6" wide-angle screen and unnecessarily well made

Powerful

Created to meet the need of the majority applications, the 15.6 Amplitud built-in QuadCore J1900, Projected capacitive(P-CAP) touch, furthermore 4GB RAM and 64GB SSD as the base model

#### Unrivalled convenience Removable HDD



P-CAP touch True-Flat bezel design



click-out RAM (Just for J1900 CPU)



More interfaces

## Multiple applications 15.6" Amplitud supports VESA75 mount at the rear housing.

15.6" Amplitud supports VESA75 mount at the rear housing.

The standard model is come with desktop stand(called A2). However,
you can remove the A2 stand and work for wall-mount application,
or have your choice on the A8V2 stand for the "Touch-and-Print" applications.





### More options

Other more options such 8" 2nd TFT screen, Wifi, customized interfaces..... are based on your request.



## Light Break-down Packaging

The ultimately product cost is one of the key criteria for the customers' purchase decision. 15.6" Amplitud with A2 desktop stand is packed by the "Semi-breakdown" packaging which helps a lot to save the transportation cost no matter whether the transportation way by AIR or by SEA

