



### Features

- True Flat Touch Screen with Streamline
- Ultra narrow edge design
- ARM Quad core Cortex-A55 to 2.0 GHz
- Metal housing
- OS: Android 11
- Support Wifi / Bluetooth
- Front panel IP54 protection design, oil proof, waterproof and corrosion resistant
- Support VESA wall mounted

## Technical Specification

Display SPEC	
Model	KA270
Display ratio	16:9
Active Area(mm)	597.888×336.312 mm
Pixel Number	1920*1080
Pixel Pitch	0.3114x 0.3114 mm
Color	16.7M
WHITE Luminance	300 cd/m <sup>2</sup> (PANEL Typ.)
Contrast	1000:1 (Panel Typ.)
Response Time(tr+tf)	14 ms
Viewing Angle	178°(H)/178°(V)

Performance Specification	
CPU	Quad core Arm Cortex-A55 to 2.0 GHz
GPU	ARM Mali-G52-2EE GPU
Memory	2G (4G Option)
Storage	EMMC 16G (32G/64G Option)
LAN	RJ45 x 1
WIFI	Yes,2.4G (5G Option)
Bluetooth	BT 4.0
OS	Android 11

Touch SPEC	
Touch Points	10 Points
Response time	≤10ms
Surface material	Glass to Glass
Surface hardness	6H
Touch the medium	Finger or A capacitor pen
Touch life	Any point can withstand more than 50 million touches

I/O	
TF	TF*1
HDMI	HDMI
USB	USB3.0 *1, USB2.0 *3
LAN	RJ45*1
Audio	Line Out+ Mic 2 in1

### Other Spec:

Power	DC:12V, 5A (Adapter input: AC 100V-240V)
Power consumption	Max: 60W
	Standby: 2W
Product Dimensions	TBD
Operating Condition	Temp.: 0°C ~ 50°C
	Hum.: 20% ~ 80%
Storage Condition	Temp.: -10°C~ 60°C
	Hum.: 10% ~ 90%

### I/O INTERFACE:

