



# SGT-116

## Windows Touch POS Terminal



**Stable, reliable POS terminal that's made to last**

**Ardax Tech GmbH**

Am Schiffbeker Berg 6, 22111 Hamburg Tel.: +49 40 4665 6240 Fax.: +49 40 466 56 24 55 E-mail: [info@ardax-tech.eu](mailto:info@ardax-tech.eu)



# TECHNICAL SHEET SGT-116

WINDOWS -J4125

WINDOWS -J6412

<b>Processor</b>	Celeron® J4125 4M Cache, up to 2.0 GHz	Celeron® J6412 1.5M Cache, up to 2.0 GHz
<b>Memory</b>	1 x SO-DIMM, DDR4, 4GB Up to 16GB	1 x SO-DIMM, DDR4 4GB Up to 16GB
<b>Storage</b>	MSATA SSD, 64GB (default), 128G/256G/512GB	
<b>Printer</b>	80mm Thermalprinter with Autotutter support thermal receipt & thermal sticker commands: ESC/POS, OPOSdriver Paper size: 80*60mm	
<b>I/O</b>	USB5, (3.0 x2, 2.0 x3) Serial ports: RJ232x 1 Display: VGAx 1 up to 1920x1080 LAN: RJ45x 1 Cash Drawer: RJ 1x 1 AUDIO* 1	
<b>Display</b>	1.6" IPS (BOE brand)	
<b>Brightness</b>	250 NITS	
<b>Resolution</b>	1366*768	
<b>Touch screen</b>	True Flat Capacitive Touch	
<b>Expansion</b>	M 2 EKey for Wi-Fi® /Bluetooth® (Module optional) MiniPCle	
<b>LAN</b>	1xRJ45 1000M	
<b>Wireless</b>	1 x WLAN 802.11a/b/g/n/ac + Bluetooth® 4.2/ BLE(Optional)	
<b>OS Windows</b>	Windows® 10 IOT, Windows® 10 PRO	
<b>Power adaptor</b>	Device: 84W/12 V DC Jack Adapter Power supply: from 100 Vac to 240 Vac	
<b>Dimensions</b>	292mm(L)*288mm(W)*100mm(H)	
<b>Weight</b>	4.2 KG	
<b>Optional:</b>	4.3" LCD display / VFD display / 2D barcode scanner / NFC card reader	

Optional

A



B



C



D



E



**Ardax Tech GmbH**

Am Schiffbeker Berg 6, 22111 Hamburg Tel.: +49 40 4665 6240 Fax.: +49 40 466 56 24 55

E-mail: [info@ardax-tech.eu](mailto:info@ardax-tech.eu)

