



**Stable, reliable POS terminal that's made to last**

**Great reliability** and an industrial project: **Ardax V10** is ideal for point-of-sale applications that require larger workload in multiple environments. The terminal is developed to support any kind of software application thanks to MTK6737 performance levels. **V10** establishes a new standard for touchscreen terminals, with **google service & google playstore, google chrome**, Support **Fiscal Moduel**, it won't be hard to open the device in case of assistance. This terminal is developed to be flexible, and can easily updated to become your company's most loyal helper.



**Printer**

Built-in 58mm Seiko high speed printer

**NFC**

Compatible to support contactless payment

**Display**

10.1" 1280\*800 Touch display  
2.4" LCD display

# V10

## TECHNICAL SHEET

|                           |  |
|---------------------------|--|
| <b>Processor</b>          | Quad-core ARM cortex-A53, Up to 1.6GB  |
| <b>Memory</b>             | 2GB RAM + 32GB ROM   |
| <b>OS</b>                 | Android 11   |
| <b>Printer</b>            | 58mm Thermal printer<br>High speed printing, up to 100mm/sec<br>commands: ESC/POS<br>Paper size: 58*40mm |
| <b>Peripheral Ports</b>   | USB2.0* 1<br>OTG USB *1<br>RJ11 or RS232* 1<br>Nano sim*1<br>PSAM *1<br>TFslot *1                        |
| <b>Button</b>             | Power key, Vol+/-key, ResetKey   |
| <b>Display</b>            | 10.1" 1280*800main display and 2.4" LCDdisplay ( 2nd )   |
| <b>Touch screen</b>       | Frue flat capacitive touch   |
| <b>Battery</b>            | yes  |
| <b>2D Barcode scanner</b> | optional   |
| <b>Speaker</b>            | 1*5W   |
| <b>Camera</b>             | 0.5M FF,support 1D/2D barcode scanning   |
| <b>NFC</b>                | optional   |
| <b>4G</b>                 | Support  |
| <b>RJ11/RS232</b>         | yes  |
| <b>Wi-Fi</b>              | 802.11a/b/g/n/ac (2.4Ghz/5Ghz) + Bluetooth® 4.2/ BLE   |
| <b>Fiscal</b>             | optional   |
| <b>Power adaptor</b>      | 12 V-3A DC JackAdapter<br>Power supply: from 100 Vacto 240 Vac   |
| <b>Dimensions</b>         | 248mm(L)*179mm(W)*75mm(H)  |
| <b>Weight</b>             | 800G   |
| <b>Certificate</b>        | FCC CE BIS   |