



### Features

- Supports 11 command modes included EPSON etc.
- Power supply from 5V to 24V to prevent any mindless use of improper power input.
- 20-column x 2-line dot matrix in a wide viewing angle.
- Easy connectivity to a wide range of POS products.
- OPOS/JPOS driver is standard

### Technical Specification

General	Display Method	LCD (Blue-White)
	Number of characters	40 (20 columns x 2 lines)
	Brightness	1200 cd/m <sup>2</sup>
	Character font	16 x 16 dot matrix
	Character type	95 Alphanumeric, 32 International Characters
	Character size	9.92 (H) x 7.136 (W) mm
	Dot Size (X x Y)	0.426 (H) x 0.6 (V) mm
	Download characters	9 characters
	Active area	142.7 (H) x 19.82 (V)
	Pole Dimension	Per support length: 339 (L) x 34 (Dia) mm
	Base Dimension	139 (W) x 119 (D) x 24.5 (H) mm
	Viewing Angle	Max. 60°
	Horizontal Rotation	Max. 355°
	Weight	Approx. 780 g
Commands Mode		LD220, EPSON POS D101, AEDEX, UTC/S, UTC/P, ADM788, DSP800, CD5220, EMAX, LOGIC CONTROL
Language Support		France, Germany, UK, Denmark-I, Sweden, Italy, Spain, Japan, Norway, Denmark-II, Slavonic, Russia, Portuguese, Canadian French, Nordic, Turkish, Greek, West European Latin, CP858, CP860, WPC1252, CP857 (Turkish), Polish, WPC1250, WPC1253 (Greek), WPC1255 (Hebrew), WPC1251, CP866, CP852, CP737 (DOSgreek), CP858, CP864 (Arabic), Farsi (Iran), CP936-GBK, CP932, CP949, CP050
Interface		USB / RS-232 (optional)
Connection	Baud rate	Direct connection 9600 or 19,200 bps
Reliability	MTBF	30,000 hours
Power	Consumption	5~24 VDC
Safety	EMC standards Safety standards	FCC, CE, ROHS