



Features

- Attractive colorful TFT LCD display, characters and background colors can be easily changed
- Large display area for more information, can show QR code and full screen images when standby
- Supports 15 command models included EPSON etc.
- OPOS/JPOS driver
- Low power consumption, only 1.5W
- Smooth character, 40*80 dot matrix
- Easy connectivity to a wide range of POS products

Technical Specification

Pattern	20 columns x 2 lines, shows full screen during standby mode
Brightness	> 350cd/m2
Resolution	800 x 480
Character font	40*80 dot matrix
Character type	95 alphanumeric, 32 international characters
Character size	10.8 (H) x 5.4 (W) mm
Active area	108 (L) x 24.8 (W) mm
Interface	USB, RS232 (optional)
Connection Baud	9600 / 19200 / 38400 / 57600 / 115200 bps
Commands mode	LD220, ESC/POS, AEDEX, UTC/S, UTC/P, ADM788, DSP800, CD5220, EMAX, LOGIC CONTROL etc.
Language support	CP437, Katakana, CP850, CP860, CP863, CP865, WCP1252, CP857, WCP1250, WCP1253, WCP1255, WCP1251, CP866, CP852, CP737, CP858, CP864, WCP1257, WCP1258, Thai (CP874), CP936
Packaging Dimension (W x H x D)	225 x 130 x 80 mm
Packaging Weight	Net: 0.65 Kg
Certificates	CE, ROHS, FCC