

BS-HJX2DW

Wireless Barcode Scanner



Features

- Wireless transmission
- Ergonomic design, comfortable hand feel
- Beautiful appearance, with excellent performance such as flame retardant, waterproof and shock resistance
- Large-capacity battery for long-term high-frequency use
- Audible and visual indication after successful decoding

Technical Specification

Image Sensor	752*480 CMOS
Light Source	625±10 nm RED LED
Aiming Light Source	625±10 nm RED LED
Symbologies	1D: Code 128, EAN-13, EAN-8, Code 39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ISBN/ISSN, Code 93, UCC/EAN-128, GS1 Databar, etc. 2D: PDF417, QR Code (Model 1/2, Micro), Data Matrix (ECC200, ECC000, 050, 080, 100, 140)
Resolution	≥ 5mil
Depth of Field	EAN13 (100%): 55 mm – 270 mm QR (20 mil): 35 mm – 275 mm
Decoding Rate	60 Scanns/sec
Field of View	Roll: 360°, Pitch: ±50°, Skew: ±50°
Charge Interface	Micro USB
Charge Voltage	5V (Charge from Scanner)
Dimensions	Scanner: 152mm*80mm*56mm Receiver: 145mm*69mm*78mm
Weight	280±10g (No line and power)
Data Transfer Method	433 MHz
Data Transmission Distance	80m
Battery Capacity	2500 mAh
Operating Temperature	-20°C ~ 50°C
Storage Temperature	-20°C ~ 70°C
Humidity	5% ~ 93% (non-condensing)
Certificate	FCC Part15 Class B, CE EMC Class B