



Features

- Sharp design with comfortable feeling in hand
- High decoding ability and high performance
- High reading ability
- Provide stand for your option
- OEM project is welcomed

Technical Specification

Image (Pixels)	640 x 480 (H x V) pixels
Light Source	(Aimer) Red color LED, (Illumination) White color LED
Roll / Pitch / Yaw	360°, ±65°, ±65°
Print Contrast	20% minimum reflective difference
Interface Supported	USB
Motion Tolerances	> 0.4 m/s
Symbology Decode Capability	<p>1D: Codabar, Code 39, Code 32, Pharmaceutical (PARAF), Interleaved 2 of 5, NEC 2 of 5, Code 93, Straight 2 of 5 Industrial, Straight 2 of 5 IATA, Matrix 2 of 5, Code 11, Code 128, GS1-128, UPC-A, UPC-E, EAN/JAN-8, EAN/JAN-13, MSI, GS1 DataBar Omnidirectional, GS1 DataBar Limited, GS1 DataBar Expanded, China Post (Hongkong 2 of 5), Korea Post</p> <p>2D: Codeblock A, Codeblock F, PDF417, Micro PDF417, GS1 Composite Codes, QR Code, Data Matrix, MaxiCode, Aztec, HANXIN</p> <p>Symbology is turned on by default Codabar, Code 39, Interleaved 2 of 5, NEC 2 of 5, Code 93, Code 128, GS1-128, UPC-A, UPC-E0, EAN/JAN-8, EAN/JAN-13, GS1-DataBar, PDF417, QR, DM, Aztec</p>
Code 39 (5 mil)	20 mm – 110 mm
Code 39 (13 mil)	30 mm – 250 mm
Dimensions & Weight	160 x 64 x 97 mm; 140.5 g
Voltage	5V
Standby Current	145 mA
Starting Current	190 mA
Work Current	380 mA
Operating & Storage Temp.	-20°C to 60°C; -30°C to 70°C
Humidity	5% to 95% relative humidity, non-condensing
Certificates	CE, ROHS, FCC