



Dimension (unit: mm)

### Features

- Platform table mount barcode scanner suitable for various new retail industries
- Megapixels, super large viewing angle, smooth switching between paper barcodes and mobile barcodes
- Large viewing angle, smooth switching between paper barcodes and mobile barcodes

### Technical Specification

Image (Pixels)	1280 pixels (H) x 1024 pixels (V)
Light Source	Warm Yellow LED
Field of View	39°(H) ,28°(V)
Roll / Pitch / Yaw	360°, ± 65°, ± 65°
Print Contrast	20% minimum reflective difference
Motion Tolerances	4M/S
Resolution	≥ 4mil
1-D	Codabar, Code 39, Code 32 Pharmaceutical (PARAF), Interleaved 2 of 5, NEC 2 of 5, Code 93, Straight 2 of 5 Industrial, Straight 2 of 5 IATA, Matrix 2 of 5, Code 11, Code 128, GS1-128, UPC-A, UPC-E, EAN/JAN-8, EAN/JAN-13, MSI, GS1 DataBar Omnidirectional, GS1 DataBar Limited, GS1 DataBar Expanded, China Post (Hong Kong 2 of 5), Korea Post
2-D	Codeblock A, Codeblock F, PDF417, Micro PDF417, GS1 Composite Codes, QR Code, Data Matrix, MaxiCode, Aztec, HANXIN
Operating Temperature	-20°C to 60°C
Storage Temperature	-30°C to 70°C
Humidity	5% to 95% relative humidity, non-condensing
Ambient Light Immunity	0-100,000 Lux
Dimensions	186mm x 152mm x 87mm
Voltage	5V
Stand-by Current	380mA
Interfaces Supported	USB
Weight	437g
Starting Current	500mA
Work Current	500mA
Prompting Mode	LED/Speaker