



BM-iC3T

BM-iC3T Series

3" thermal printer w/ 50mm diameter paper

iOS/Windows/Android/Linux

The Right thermal Printer to Grow Your business for IoT Solutions

1. Mobile printer for IoT solutions

Our world is experiencing a digital transformation that is fundamentally reinventing the customer experience un-pending traditional business models and operations, and placing greater demands on “mobile printing”. BM-iC3T printer is built-in advanced technology and with more compatibility for your applications.



2. Upgrade functions for mobility:

- a. 50mm diameter paper roll
- b. 70mm/second print speed
- c. Warning alarm for paper-lacking and power near off.
- d. Sleep and auto power off after 60 second of printer is no working.
- e. Support page mode and WiFi with AP and STA modes.

3. USB and Wireless connections:

BM-iC3T with 3-in-1 interface(USB + Bluetooth + WiFi) as standard which is more helpful to you for your any wireless applications. Furthermore, it can lower your inventory load for the different wireless solutions.

4. User-friendly, and Easy to use

BM-iC3T support easy paper loading and bundled with hand-carry bag as standards for your operations.

Ordering Information:

BM-iC3T: 3" thermal mobile printer without cutter,
(USB + WiFi + Bluetooth)



Technical Specifications

MODEL	BM-iC3T
Printing method	Direct thermal
Printing speed	70mm/s
Paper width	79.5 ± 0.5mm
Paper roll diameter	50mm
Paper thickness	0.06~0.08mm
Character per line	576 dots/line 512 dots/line
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24x24 dots
Interface	USB+Wifi+Bluetooth
Bar code	1D Barcode: UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) / CODABAR/ITF/CODE39/CODE93/CODE128 2D Barcode: QR CODE/PDF417
Extended characters	PC347(Standard Europe), Katakana, PC850(Multilingual) , PC860(Portuguese), PC863(Canadian-French), PC865(Nordic), WestEuropeGreek, Hebrew, East Europe, Iran, WPC1252, PC866(Cyrillic#2), PC852(Latin2), Pc858, IranII, Latvian, Arabic, PT151(1251)
NV FLASH	64 K Bytes
Input buffer	32 K Bytes
Power supply	Input: AC 110V/240V, 50~60Hz
Power	Output: AC 9V-2A
Battery	1800mAh
Reliability	Printing head life: 50 km
Working environment	Temperature (0~45°C), humidity(10~80%)
Storage environment	Temperature (-10~60°C), humidity(10~90%)
Operating system	Win XP/Win 7/Win 8/Win 10/Linux/IOS/Android
Gross weight	0.325 kg
Dimension	136×116×60mm (L × W × H)



Birch is a trademark of Birch Technology Inc.
All other products, brands or companies are trademarks or registered trade marks of their respective companies.
Specifications are subject to change without prior notice

BIRCH TECHNOLOGY INC.
7F-13, No.79 Hsin Tai 5th Rd. Hsichih Dist., New Taipei City, Taiwan
Tel:886-2-2698-9596 Fax:886-2-2698-9597
E-mail:sales@mail.birch.com.tw http://www.e-birch.com http://www.birch.com.tw

Contact us for details