



Portable Thermal Printer

GP-M322



Mobile device compatible

- Support windows, Android, IOS connection
- Connectivity options including USB+Bluetooth, USB+Wi-Fi



Powerful printing technology

- Print speed up to 80mm/s(receipt),50mm/s(label)
- Media width: 80mm; Print width: 72mm



Ardax Tech GmbH
Am Schiffbeker Berg 6
22111 Hamburg

Tel +49-40-4665624-0

Fax +49-40-4665624-55

<https://www.ardex-tech.eu>

Specification

Print	Print Method	Thermal
	Resolution	203DPI
	Print Width	72mm max.
	Print Speed	Receipt: 80mm/s Label: 50mm/s
	Memory	DRAM: 8M FLASH: 16M
	Print Head Temperature Detection	Thermistor
	Print Head Position Detection	Micro switch
	Paper Detection	Transmissive sensor
	Black Mark Detection	Reflective sensor
	Interface	USB + Bluetooth (USB+Wi-Fi Optional)
Barcode & Character & Graphics	Barcode Type	1D: CODE128, EAN128, ITF, CODE39, CODE93, EAN13, EAN13+2, EAN13+5, EAN8, EAN8+2, EAN8+5, CODABAR, POSTNET, UPC-A, UPC-A+2, UPC-A+5, UPC-E, UPC-E+2, UPC-E+5, CPOST, MSI, MSIC, PLESSEY, ITF14, EAN14 2D: QRCODE
	Font	Font 0~ Font 8
	Enlargement & Rotation	1 to 10 times enlargement in both directions; 0°, 90°, 270°, 360° rotation
	Graphics	Monochrome PCX, BMP can download flash, dram
Print Media	Paper Type	Thermal paper
	Paper Width	25mm-80mm(±0.5mm)
	Paper Roll	OD 50mm max.; ID 9mm max.
	Feeding Type	Upper, peel-off
Power	Input	5VDC, 2A
Physical Properties	Dimension	126(L) x 109(W) x 61(H)mm
Physical Properties	Printer Weight	410g
Power Properties	Standby Time	7 days
Environment	Temperature	Operation Condition: 5~45°C(41~104°F), 25~85% Storage Condition: -10~50°C(-10~140°F), 10~90%
	Pressure	86~106/kPa



Main Features

- * Compact size, light weight and freely portable
- * Easy connection Bluetooth / Wi-Fi
- * Display screen for convenient operation
- * 2100mAh battery to ensure long standby time